

LHC Injectors Upgrade

Update on Studies of the 200 MHz TW RF system

R. Calaga, F. Caspers, A. Grudiev, T. Kaltenbacher, A. Lasheen, E. Montesinos, <u>T. Roggen</u>, E. Shaposhnikova, Ya. Shashkov, C. Völlinger



LIU-SPS-BD-WG



- Comparison: measurements vs simulations
 - 1-section
 - 4-section
- Existing impedance model
- Efforts on further reduction of HOM impedance
- Conclusions & outlook



Measurement vs simulations: 1-section









- Comparison: measurements vs simulations
 - 1-section
 - 4-section
- Existing impedance model
- Efforts on further reduction of HOM impedance
- Conclusions & outlook





• Existing impedance model can be reproduced with todays simulation model





Existing impedance model can be reproduced with todays simulation model





- Comparison: measurements vs simulations
 - 1-section
 - 4-section
- Existing impedance model
- Efforts on further reduction of HOM impedance
- Conclusions & outlook





Efforts on further reduction of HOM impedance

Fig courtesy: Ya. Shashkov

- Currently installed 628 MHz HOM dampers work very well
- Damper location in the cavity already optimal
- Installing more HOM couplers (Simulations: Ya. Shashkov, MEPhI, Russia)

 \rightarrow Improvement: 30 %



Fig courtesy: Ya. Shashkov

Top: same dampers Right: different design needed (hook/loop)



- Comparison: measurements vs simulations
 - 1-section
 - 4-section
- Existing impedance model
- Efforts on further reduction of HOM impedance
- Conclusions & outlook



Conclusions & Outlook

- 1. Measurement based verification
 - 628 MHz HOM dampers work very well
 - Feeder line limited contribution to damping
 - 1 section: very good agreement meas.- simulations
 - 4-section: in progress: model possibly needs to be extended with transverse HOM couplers
- 2. Existing impedance model reproduced
- 3. Further reduction of HOM impedance
 - Studies ongoing
 - Doubled # dampers
 - Loop-dampers at pickup loop location





